1998/G 004 (5587*264)

SERIAL NO: 09/647,743

Al.

accordance with VDA 275, of less than 15 mg/kg and a modulus of elasticity in accordance with ISO 527 of from 2400 to 3100 N/mm², a yield stress in accordance with ISO 527 of from 60 to 70 N/mm² and a notched impact strength in accordance with ISO 179 at 23°C of from 4 to 12 mJ/mm².

An

4. A molding composition as claimed in claim 1, including antioxidants, acid scavengers, stabilizers and colorants.

Add the following claim.

p3

11. A molding composition as claimed in claim 1 having a form selected from the group consisting of colored moldings, interior transport fittings, interior transport cladding, toys, baby items and electronic/components.

Please see Appendix 1 for the changes made to the claims. Terms underlined are to be added. Terms bracketed are to be deleted.

REMARKS

The present application has been carefully studied and amended in view of the outstanding Office action dated July 2, 2001, and reconsideration of that Action is requested in view of the following comments.

Claims 2, 3 and 5-10 have been cancelled. Claim 1 has been amended to include the features of claims 2 and 3. Additionally, new claim 11 recites the substance of claims 5-10 in proper form. As amended and presented all of the claims are believed to be in proper form, and in full compliance with 35 USC §112.